

Energy Efficiency Design Summary: Prescriptive Method

(Building Code Part 9, Residential)

This form is used by a designer to demonstrate that the energy efficiency design of a house complies with the Building Code using the prescriptive method described in Subsection 3.1.1. of SB-12. This form is applicable where the ratio of gross area of windows/sidelights/skylights/glazing in doors and sliding glass doors to the gross area of peripheral walls is not more than 22%.

For use by Principal Authority	
Application No:	Model/Certification Number

A. Project Information

Building number, street name		Unit number	Lot/Con
Municipality	Postal code	Reg. Plan number / other description	

B. Prescriptive Compliance [Indicate the Building Code compliance package being employed in this house design]

SB-12 Prescriptive (input design package):	Package _____	Table: _____
--	---------------	--------------

C. Project Design Conditions

Climatic Zone (SB-1):	Heating Equipment Efficiency	Space Heating Fuel Source
<input type="checkbox"/> Zone 1 (< 5000 degree days)	<input type="checkbox"/> ≥ 90% AFUE	<input type="checkbox"/> Gas <input type="checkbox"/> Propane <input type="checkbox"/> Solid Fuel
<input type="checkbox"/> Zone 2 (≥ 5000 degree days)	<input type="checkbox"/> ≥ 78% < 90% AFUE	<input type="checkbox"/> Oil <input type="checkbox"/> Electric <input type="checkbox"/> Earth Energy
Ratio of Windows, Skylights & Glass (W, S & G) to Wall Area		Other Building Characteristics
Area of walls = _____ m ² or _____ ft ²	W, S & G% = _____	<input type="checkbox"/> Log/Post & Beam <input type="checkbox"/> ICF Above Grade <input type="checkbox"/> ICF Basement <input type="checkbox"/> Slab-on-ground <input type="checkbox"/> Walkout Basement <input type="checkbox"/> Air Conditioning <input type="checkbox"/> Combo Unit <input type="checkbox"/> Air Source Heat Pump (ASHP) <input type="checkbox"/> Ground Source Heat Pump (GSHP)
Area of W S&G = _____ m ² or _____ ft ²	Utilize window averaging: <input type="checkbox"/> Yes <input type="checkbox"/> No	

D. Building Specifications [provide values and ratings of the energy efficiency components proposed]

Energy Efficiency Substitutions			
<input type="checkbox"/> ICF (3.1.1.2.(5) & (6) / 3.1.1.3.(5) & (6)) <input type="checkbox"/> Combined space heating and domestic water heating systems (3.1.1.2.(7) / 3.1.1.3.(7))			
<input type="checkbox"/> Airtightness substitution(s) Airtightness test required (Refer to attached Design Guide)	<input type="checkbox"/> Table 3.1.1.4.B Required _____ Permitted Substitution: _____ <input type="checkbox"/> Table 3.1.1.4.C Required _____ Permitted Substitution: _____ Required _____ Permitted Substitution: _____		
Building Component	Minimum RSI / R values Or Maximum U-Value ⁽¹⁾		Efficiency Ratings
Thermal Insulation	Nominal	Effective	Building Component
Ceiling with Attic Space			Windows & Doors Provide u-Value ⁽¹⁾ or ER rating
Ceiling without Attic Space			Windows/Sliding Glass Doors
Exposed Floor			Skylights/Glazed Roofs
Walls Above Grade			Mechanicals
Basement Walls			Heating Equip. (AFUE)
Slab (all >600mm below grade)			HRV Efficiency (SRE% at 0°C)
Slab (edge only ≤600mm below grade)			DHW Heater (EF)
Slab (all ≤600mm below grade, or heated)			DWHR (CSA B55.1 (min. 42% efficiency))
			Combined Heating System
			# Showers _____

(1) U value to be provided in either W/(m².K) or Btu/(h.ft².F) but not both

E. Designer(s) [names & BCIN(s), if applicable, of person(s) providing information herein to substantiate that design meets the building code]

Qualified Designer Declaration of designer to have reviewed and taken responsibility for the design work		
Name	BCIN	Signature

Energy Efficiency Design Summary: Prescriptive Method

(Building Code Part 9, Residential)

Guide to the Prescriptive Energy Efficiency Design Summary Form

This form must accurately reflect the information contained on the drawings and specifications being submitted. Refer to Supplementary Standard SB-12 for details about Building Code compliance requirements. Further information about energy efficiency requirements for new buildings is available from the Provincial Building Code website or the Municipal Building Department.

The Building Code permits a house designer to use one of four energy efficiency compliance options:

1. Comply with the SB-12 Prescriptive design tables (this form is for this option (eg. Option 1))
2. Use the SB-12 Performance compliance method, and model the design against the prescriptive standards,
3. Design to ENERGY STAR®, or
4. Design to R-2000® standards.

COMPLETING THE FORM

B. Compliance Options

Indicate the compliance option being used.

SB-12 Prescriptive requires that the building conforms to a package of thermal insulation, window and mechanical system efficiency requirements set out in Subsection 3.1.1. of SB-12. Energy efficiency design modelling and testing of the building is not required under this option. Certain substitutions are permitted. In which case, the applicable airtightness targets in Table 3.1.1.4.A. must be met.

C. Project Design Conditions

- *Climatic Zone:* The number of degree days for Ontario cities is contained in Supplementary Standard SB-1.
- *Windows, Skylights and Glass Doors:* If the ratio of the total gross area of windows, sidelights, skylights, glazing in doors and sliding glass doors to the total gross area of walls is more than 17%, higher efficiency glazing is required. If the ratio is more than 22% the SB-12 Prescriptive option **may not** be used. The total area is the sum of all the structural rough openings. Some exceptions apply. Refer to 3.1.1.1. of SB-12 for further details.
- *Fuel Source and Heating Equipment Efficiency:* The fuel source and efficiency of the proposed heating equipment must be specified in order to determine which SB-12 Prescriptive compliance package table applies.
- *Other Building Conditions:* These construction conditions affect SB-12 Prescriptive compliance requirements.

D. Building Specifications

- *Thermal Insulation:* Indicate the RSI or R-value being proposed where they apply to the house design. Under the SB-12 Prescriptive option, alternative ICF wall insulation is permitted in certain conditions where other design elements meet higher standards. Refer to SB-12 for further details. Where effective insulation values are being used, the Authority Having Jurisdiction may require supporting documentation.

BUILDING CODE REQUIREMENTS FOR AIRTIGHTNESS IN NEW HOUSES

All houses must comply with increased air barrier requirements in the building code. Notice of air barrier completion must be provided and an inspection conducted prior to it being covered.

The air leakage rates in Table 3.1.1.4.A. are not requirements. This provision is a voluntary provision for when credits for airtightness are claimed. Credit for airtightness allows the designer to substitute the requirements of compliance packages as set out in Table 3.1.1.4.B. or 3.1.1.4.C. Neither the air leakage test nor compliance with airtightness targets given in Table 3.1.1.4.A are required, unless credit for airtightness is claimed. Table 3.1.1.4.A provides airtightness targets in three different metrics; ACH, NLA, NLR. Any one of them can be used.

OBC Reference Default Air Leakage Rates (Table 3.1.1.4.A)

Building Type	Airtightness Targets				
	ACH @ 50 Pa	NLA @ 10 Pa		NLR @ 50 Pa	
Detached dwelling	2.5	1.26 cm ² /m ²	1.81 in ² /100 ft ²	0.93 L/s/m ²	0.18 cfm50/ft ²
Attached Dwelling	3.0	2.12 cm ² /m ²	3.06 in ² /100 ft ²	1.32 L/s/m ²	0.26 cfm50/ft ²

The building code requires that a blower door test be conducted to verify the air tightness of the house during construction if the SB12 Prescriptive option with airtightness credit is being applied. Results of the airtightness test may need to be submitted to the Authority Having Jurisdiction. Airtightness of less than 2.5 ACH @ 50 Pa (or NLA or NLR equivalent) in the case of detached houses, or 3.0 ACH @ 50 Pa (or NLA or NLR equivalent) in the case of attached houses is necessary to meet the required energy efficiency standard.

E. House Designer

The building code requires designers providing information about whether a building complies with the building code to have a BCIN. Exemptions apply to architects, engineers and owners designing their own house.